



Unit: mm

型式 Model	行程 Stroke	理論出力 / Capacity Kgf					A	B	C	D	E	F	G	H max.	H min.	K max.	PT
		3kg/cm ²	4kg/cm ²	5kg/cm ²	6kg/cm ²	7kg/cm ²											
AP1-63	50	84	112	140	168	196	10	30	100	170	160	230	35	150	100	440	1/4
AP1-80	100	132	176	220	264	308	20	35	144	200	200	338	80	235	135	738	3/8
AP1-100	100	217	288	361	433	506	20	35	144	200	200	338	80	235	135	738	3/8
AP1-125	100	349	466	583	699	817	25	40	182	250	250	418	100	320	220	894	3/8
AP1-150	100	500	666	833	1000	1167	25	40	182	250	250	434	100	320	220	894	3/8
AP2-180	100	735	980	1225	1470	1715	25	50	192	250	250	530	170	290	190	1059	1/2
AP2-200	100	912	1216	1520	1824	2128	25	50	204	280	280	590	170	290	190	1059	1/2
AP2-250	100	1426	1901	2376	2851	3326	25	50	250	320	320	690	240	320	220	1159	1/2
AP3-150	200	530	706	883	1060	1237	25	45	---	280	280	550	45	220	20	711	3/8
AP3-200	250	942	1256	1570	1886	2199	25	50	---	280	280	550	45	270	20	835	1/2
AP3-250	250	1473	1964	2454	2945	3436	25	60	---	280	280	550	50	320	70	840	1/2

SUNNY ENTERPRISE CO., LTD.

9, LANE 56, AN-KANG RD., NEI-HU DIST., TAIPEI 114

TEL:886-2-27912121(10-LINES) FAX:886-2-27910871

E-mail: sunny@sunnyent.com.tw

http://www.sunnyent.com.tw